



www.prowellwoodworks.com
445 Portal St. #5, Cotati, CA 94931
PST: 800 . 466 . 1850 FAX: 707 . 861 . 3409

System Entry
12/30/2025

URL Posted Date
1/2/2026

Billing info

Tom Fountain
1441 Edgewood Dr
Palo Alto, CA 94301
[ountain@cs.stanford.edu](mailto:fountain@cs.stanford.edu)
(650) 544-8741

Description	Price
#1) <u>Exterior Front Left Gate</u> : 60-3/4" net width x 78" ht from grade to apex (69" to spring-point). Swing: LH-Out. Embedded wiring to mortise lock. 2-1/4" gate thickness. 5-1/2"W stiles.	\$5,633.00
Pair of jambs (1-1/2"T x 3-3/4"W)	\$250.00
#2) <u>Exterior Front Right Main Gate</u> : 39-9/32" net width x 78"ht from grade to apex (69" to spring-point). Swing: RH-Out. Embedded wiring to mortise lock. 2-1/4" gate thickness. 5-1/2"W stiles	\$4,579.00
Pair of jambs (1-1/2"T x 3-3/4"W)	\$250.00
#3) <u>Exterior Front Right Outside Trash Enclosure Gate</u> : 44-23/32" net width x 78"ht from grade to apex (69" to spring-point). Swing: RH-Out. Embedded wiring to mortise lock. 2-1/4" gate thickness. 5-1/2"W stiles	\$4,579.00
Pair of jambs (1-1/2"T x 3-3/4"W)	\$250.00
#4) <u>Exterior Front Right Inside Trash Enclosure Gate</u> : 40-9/32" net width x 69"ht from grade to spring-point (Allow apex ht to adjust to conform to radius of gate #2). Swing: LH-In. Embedded wiring to mortise lock. 2-1/4" gate thickness. 5"W stiles	\$4,579.00
Pair of jambs (1-1/2"T x 3-3/4"W)	\$250.00
#5) <u>Pool House Shower Gate</u> : 27-5/8" net width x 72" ht to from grade to apex (69" ht from grade to spring-point) (Allow apex ht to adjust to conform to radius of gate #2). Swing: LH-In. 2-1/4" gate thickness. 5-1/2"W stiles. *No embedded wiring	\$4,154.00
Pair of jambs (1-1/2"T x 3-3/4"W)	\$250.00
#6) <u>Creek Rear Gate</u> : 38-7/8" net width x 96" ht from grade to apex (Allow apex ht to adjust to conform to radius of gate #2). Swing: RH-Out. 2-1/4" gate thickness. Stiles 5"W.	\$4,908.00
Pair of jambs (1-1/2"T x 3-3/4"W)	\$250.00



www.prowellwoodworks.com
445 Portal St. #5, Cotati, CA 94931
PST: 800 . 466 . 1850 FAX: 707 . 861 . 3409

System Entry
12/30/2025

URL Posted Date
1/2/2026

Billing info
Tom Fountain
1441 Edgewood Dr
Palo Alto, CA 94301
fountain@cs.stanford.edu
(650) 544-8741

All Gates w/o lower open slots. 5 columns / 2 rows of grids. Embedded Cat 5 wiring gates #1-#4 from bottom pivot hinge to mortise lock stile.

Credit Card Number		Item Subtotal	\$29,932.00
Adv Pay Date	Adv Pay Approve	Sales Tax	\$109.44
Final Pay Date	Final Pay Approve	Delivery	\$375.00
		Grand Total	\$30,416.44
		Advance Pay	
		Final Pay	
		Balance Due	\$30,416.44

NOTES:

Payment: A 50% advance is processed (via card or check) prior to the start of all work. Final payment will be processed upon completion of your order and prior to shipping.

Cancellations: Because we are a custom, made-to-order shop, there is a fee of 25% of your advance payment not to exceed \$1,000 for cancellations prior to the approval of your drawings. **There are no refunds once the drawings have been approved.

Pricing Quotes: Quoted and agreed upon pricing remains valid for 1 month from when your payment information is entered. If after 1 month and the project has not arrived at the stage of creating drawings, or the drawings have not been approved, the original quote is subject to review.

Storage: Products are preferably shipped or delivered within 2 weeks of posting completed photos.

Hardware: There is a 25% fee for all returns of unblemished products within one month of sale. Items that have been installed and exposed to the weather are non refundable unless they are defective.

Standard Lock-sets and Electronic Access: The use of standard 2-3/8" back-set locks over traditional gate latches is not recommended. This includes certain electronic access specifications requiring minimal swing clearance. Normal expansion of your gate will occur and the clearance required for a standard 2-3/8" lock-set (1/4" max) puts the gate at risk of becoming wedged against the jamb, requiring the sort of effort with each passage that can damage the gate. We cannot support the integrity of any gate that uses a standard back-set lock-set. We insist upon the use of Gate Latches or dead bolts allowing 3/8"-1/2" clearance between the edge of the gate and the jamb or post.

Finishing: All products must be fully exposed to your regional climate for 3 weeks prior to applying any solid or opaque finishes. Our WoodRX absorbing finish is available as a pre-finish or can be applied upon receipt of products. WoodRX color charts vary on the finished product as per inherent hues and tints of western cedar.

Shipping/Crating: It is always best to have someone present to accept delivery. In the event of a potentially damaged crate, you must sign off on the delivery receipt at the time of delivery noting the possibly damaged crate. If on later inspection, there is damage to the product, you must contact UPS freight at the number on your receipt to report this damage within 5 days of delivery and request an inspector. If damage is not noted on the delivery receipt and UPS is not contacted within 5 days, liability falls on the receiver. Prowell Woodworks will not automatically replace your damaged product free of charge.

****Please review your statement and drawings for accuracy. Upon approval, please provide your signature and date, confirming the accuracy of both the statement and dated drawings.

****Drawings dated January 2, 2026.

Approval Signature _____ **Date** _____